

## § 108.646

## 46 CFR Ch. I (10–1–08 Edition)

(2) The name of the port required to be marked on the unit to meet the requirements of subpart 67.123 of this chapter.

(3) The length of the painter must be marked on each rigid liferaft.

(4) At each entrance of each rigid liferaft, the number of persons the rigid liferaft is equipped for, not exceeding the number shown on its nameplate, must be marked in letters and numbers at least 100 millimeters (4 inches) high, in a color contrasting to that of the liferaft.

[CGD 84–069, 61 FR 25298, May 20, 1996, as amended at 63 FR 52815, Oct. 1, 1998]

### § 108.646 Marking of stowage locations.

(a) Containers, brackets, racks, and other similar stowage locations for lifesaving equipment, must be marked with symbols in accordance with IMO Resolution A.760(18), indicating the devices stowed in that location for that purpose.

(b) If more than one device is stowed in that location, the number of devices must also be indicated.

(c) Survival craft should be numbered.

[CGD 84–069, 61 FR 25298, May 20, 1996, as amended at 63 FR 52815, Oct. 1, 1998]

### § 108.647 Inflatable liferafts.

The number of the liferaft and the number of persons it is permitted to accommodate must be marked or painted in a conspicuous place in the immediate vicinity of each inflatable liferaft in block capital letters and numbers. The word “liferaft” or the appropriate symbol from IMO Resolution A.760(18) shall be used to identify the stowage location. Liferafts stowed on the sides of the unit should be numbered in the same manner as the lifeboats. This marking must not be on the inflatable liferaft container.

[CGD 84–069, 61 FR 25298, May 20, 1996]

### § 108.649 Lifejackets, immersion suits, and lifebuoys.

(a) Each lifejacket must be marked—

(1) In block capital letters with the name of the unit; and

(2) With type I retro-reflective material approved under approval series

164.018. The arrangement of the retro-reflective material must meet IMO Resolution A.658(16).

(b) The stowage positions for lifejackets, other than lifejackets stowed in staterooms, must be marked with either the word “LIFEJACKET” or with the appropriate symbol from IMO Resolution A.760(18).

(c) Each immersion suit or anti-exposure suit must be marked to identify the person or unit to which it belongs.

(d) Immersion suits or anti-exposure suits must be stowed so they are readily accessible, and the stowage positions must be marked with either the words “IMMERSION SUITS” or “ANTI-EXPOSURE SUITS”, or with the appropriate symbol from IMO Resolution A.760(18).

(e) Each lifebuoy must be marked—

(1) In block capital letters with the unit’s name and with the name of the port required to be marked on the unit under subpart 67.123 of this chapter; and

(2) With type II retro-reflective material approved under part 164, subpart 164.018 of this chapter. The arrangement of the retro-reflective material must meet IMO Resolution A.658(16).

(f) Each lifebuoy stowage position must be marked with either the words “LIFEBUOY” or “LIFE BUOY”, or with the appropriate symbol from IMO Resolution A.760(18).

(g) Each lifejacket, immersion suit, and anti-exposure suit container must be marked in block capital letters and numbers with the minimum quantity, identity, and if sizes other than adult or universal sizes are used on the unit, the size of the equipment stowed inside the container. The equipment may be identified in words or with the appropriate symbol from IMO Resolution A.760(18).

[CGD 84–069, 61 FR 25298, May 20, 1996, as amended at 63 FR 52815, Oct. 1, 1998]

### § 108.650 EPIRBs and SARTs.

Emergency position indicating radiobeacons and search and rescue transponders. Each EPIRB and SART